

SABA, a strong bond

Description

SABA Primer 9102 is a one-component primer. SABA Primer 9102 is very suitable for priming non-porous substrates that are to be sealed with certain SABA-sealants.

Solvent based adhesives

Special properties

Brings about very good adherence when used on non-porous substrates like metal, double-baked tiles and acid proof, compressed tiles and synthetic materials

MSP sealants

Method of use

Substrate must be dry, clean and free from grease and dust. Apply primer with a brush. Let dry for at least 10 minutes, but no longer than 24 hours, before applying the sealant.

Water based adhesives

Silicone sealants

Technical data

Basis	: silanes
Consistency	: watery
Viscosity at 23 °C	: approx. 10 mPa.s
Density	: approx. 810 kg/m ³
Solids content	: approx. 2%
Flash point	: approx. +12 °C
Solvents	: mixture of alcohols and aromats
Open time	: approx. minimum 10 min., maximum 24 hours
Coverage	: approx. 50 to 100 g/m ²
Clean tools with	: SABA Cleaner 22
Work temperature	: minimum +5 °C
Storage temperature	: minimum +5 °C, maximum +35 °C
Temperature resistance	: approx. -30 °C up to +150 °C
Shelf life	: 18 months in unopened packing

Foam coatings

Hotmelts

Epoxy products

PU products

Polysulfide products

Order information

Primers

Packing	drum
Content	1 litre

Cleaning agents

Colour	transparent / clear
Article No.	100331 AAZ

Safety recommendations

See the corresponding material safety data sheet.



SABA Dinxperlo BV

Industriestraat 3, NL-7091 DC Dinxperlo, PO Box 3, NL-7090 AA Dinxperlo, the Netherlands, Tel +31 (0) 315 658999, Fax +31 (0) 315 653207, E-mail info@saba.nl, Internet www.saba.nl.

Our application instructions and technical advice are based on our actual level of knowledge. We cannot accept any liability for conclusions and recommendations resulting from these. Buyers and/or users should judge the suitability of our products for any envisaged application by preliminary testing. The general terms and conditions for the members of the "Nederlandse Vereniging van Rubber- en Kunststoffabrikanten (NVR)" apply on all our deliveries.

Version number: 200501