

SABA, a strong bond

Description

SABA Primer H17 is a two-component primer. SABA Primer H17 can be used for priming porous substrates that are to be sealed or coated with SABA-polysulfide sealants or coatings

Solvent based adhesives

Special properties

Excellent resistance to moisture, solvents, acids and bases

MSP sealants

Method of use

Surfaces should be clean, dry and free of grease and dust.
Mixing ratio: add 30 parts PART B to 100 parts PART A (weight).

Water based adhesives

Technical data

Silicone sealants

	Part A	Part B
Basis	: epoxides	amines
Viscosity at 23 °C	: watery	watery
Density (kg/m ³)	: approx. 1000	approx. 1000
Solids content	: approx. 45%	approx. 30%
Solvents	: ester	ester
Open time	: approx. 30 minutes to 6 hours	
Drying time	: approx. 30 minutes	
Coverage	: approx. 100 g/m ² , depending on surface	
Apply by	: brush / spray gun	
Pot life (after mixing)	: approx. 2 to 3 hours	
Work temperature	: minimum +5 °C	
Storage temperature	: minimum +5 °C, maximum +30 °C	
Temperature resistance	: approx. minimum -40 °C, maximum +120 °C	
Shelf life	: 18 months in unopened packing for both part A and Part B	

Foam coatings

Hotmelts

Epoxy products

PU products

Polysulfide products

Order information

Packing Content	set 520 gram	set 1040 gram	set 4,5 litres
Colour	light yellow	light yellow	light yellow
Article No.	100324	100324	100324

Primers

Cleaning agents

Safety recommendations

See the corresponding material safety data sheet.



SABA Dinxperlo BV

Industriestraat 3, NL-7091 DC Dinxperlo, PO Box 3, NL-7090 AA Dinxperlo, the Netherlands, Tel +31 (0) 315 658999, Fax +31 (0) 315 653207, E-mail info@saba.nl, Internet www.saba.nl.

Our application instructions and technical advice are based on our actual level of knowledge. We cannot accept any liability for conclusions and recommendations resulting from these. Buyers and/or users should judge the suitability of our products for any envisaged application by preliminary testing. The general terms and conditions for the members of the "Nederlandse Vereniging van Rubber- en Kunststoffabrikanten (NVR)" apply on all our deliveries.

Version number: 200402